



RF LC Band Pass Filter



10-500MHz

P/N	1dB Pass Band (MHz)	I.L. at Center Freq. (dB) Max.	Rejection 1 (dBMin@MHz)	Rejection 2 (dBMin@MHz)	VSWR Typ.	Size (mm) (L x W x H)
AEMFT-T-BP-13-23-L	13-23	1.5	-	60@36	1.5	40.4x12.0x10.
AEMFT-T-BP-19-31-L	19-31	0.8	45@15	45@30	1.5	40.4x12.0x10.
AEMFT-T-BP-28.5-31.5-L	28.5-31.5	1.5	75@20	75@40	1.5	30.0x12.0x10.
AEMFT-T-BP-40-60-L	40-60	1.0	65@25	75@70	1.5	40.4x12.0x10.
AEMFT-T-BP-50-70-L	50-70	1.5	60@30	75@90	1.5	40.4x12.0x10.
AEMFT-T-BP-30-130-L	30-130	0.5	-	40@150	1.5	50.9x9.5x9.5
AEMFT-T-BP-80-100-L	80-100	1.8	80@50	80@130	1.5	40.4x9.5x9.5
AEMFT-T-BP-95-145-L	95-145	1.0	45@75	70@200	1.5	40.4x12.0x10.
AEMFT-T-BP-105-145-L	105-145	1.5	50@80	50@170	1.5	50.9x9.5x9.5
AEMFT-T-BP-128-212-L	128-212	1.0	80@64	65@276	1.5	40.4x12.0x10.
AEMFT-T-BP-150-200-L	150-200	1.2	70@100	40@225	1.5	40.4x12.0x10.
AEMFT-T-BP-180-200-L	180-200	2.3	25@170	25@210	1.5	40.4x12.0x10.
AEMFT-T-BP-150-250-L	150-250	1.1	40@125	50@300	1.5	27.2x12.6x6.7
AEMFT-T-BP-200-220-L	200-220	2.3	25@190	25@230	1.5	40.4x12.0x10.
AEMFT-T-BP-195-245-L	195-245	1.2	85@20	70@440	1.5	27.2x12.6x6.7
AEMFT-T-BP-215-245-L	215-245	2.2	15@210	15@250	1.5	30.0x12.0x10.
AEMFT-T-BP-227-253-L	227-253	1.8	75@160	85@320	1.5	30.0x12.0x10.
AEMFT-T-BP-240-260-L	240-260	1.8	58@200	55@300	1.5	40.4x12.0x10.
AEMFT-T-BP-200-300-L	210-290	1.0	60@150	85@400	1.5	40.4x12.0x10.
AEMFT-T-BP-200-360-L	200-360	1.2	40@150	60@410	1.5	40.4x12.0x10.
AEMFT-T-BP-185-415-L	185-415	0.6	50@100	60@500	1.5	50.9x9.5x9.5
AEMFT-T-BP-250-400-L	250-400	0.9	65@200	65@500	1.5	40.4x12.0x10.
AEMFT-T-BP-258-442-L	258-442	1.1	90@100	90@600	1.5	50.9x9.5x9.5
AEMFT-T-BP-300-450-L	300-450	1.1	60@225	60@600	1.5	40.4x12.0x10.
AEMFT-T-BP-360-440-L	360-440	2.5	40@300	40@500	1.5	50.9x9.5x9.5
AEMFT-T-BP-320-540-L	320-540	1.2	28@270	28@585	1.5	40.4x12.0x10.
AEMFT-T-BP-350-530-L	350-530	0.8	65@250	80@700	1.5	50.9x9.5x9.5
AEMFT-T-BP-350-550-L	350-550	1.0	80@200	80@700	1.5	40.4x12.0x10.
AEMFT-T-BP-400-520-L	400-520	1.2	60@200	80@800	1.5	40.4x9.5x9.5



RF LC Band Pass Filter



500MHz-1250MHz

P/N	1dB Pass Band (MHz)	I.L. at Center Freq. (dB) Max.	Rejection 1 (dBMin@MHz)	Rejection 2 (dBMin@MHz)	VSWR Typ.	Size (mm) (L x W x H)
AEMFT-T-BP-480-520-L	480-520	1.8	65@400	65@600	1.5	30.0x12.0x10.
AEMFT-T-BP-390-610-L	390-610	1.0	65@280	70@720	1.5	50.9x9.5x9.5
AEMFT-T-BP-350-650-L	350-650	1.0	65@200	90@800	1.5	50.9x9.5x9.5
AEMFT-T-BP-400-700-L	400-700	0.9	45@350	45@800	1.5	40.4x12.0x10.
AEMFT-T-BP-585-615-L	585-615	2.9	45@550	45@650	1.5	30.0x12.0x10.
AEMFT-T-BP-450-750-L	450-750	0.8	65@260	65@930	1.5	50.9x9.5x9.5
AEMFT-T-BP-605-685-L	605-685	2.8	20@580	33@720	1.5	40.4x12.0x10.
AEMFT-T-BP-672.5-727.5-	672.5-727.5	1.7	53@600	53@800	1.5	30.0x12.0x10.
AEMFT-T-BP-550-950-L	550-950	0.6	50@300	50@1200	1.5	40.4x12.0x10.
AEMFT-T-BP-500-1000-L	500-1000	0.8	50@400	50@1100	1.5	40.4x12.0x10.
AEMFT-T-BP-740-800-L	740-800	2.8	50@695	50@845	1.5	40.4x12.0x10.
AEMFT-T-BP-750-850-L	750-850	2.3	45@700	75@1000	1.5	40.4x9.5x9.5
AEMFT-T-BP-769-926-L	769-926	1.1	65@500	65@1500	1.5	30.0x12.0x10.
AEMFT-T-BP-828-912-L	828-912	1.8	50@740	50@1000	1.5	40.4x12.0x10
AEMFT-T-BP-850-950-L	850-950	2.2	45@800	44@1000	1.5	40.4x9.5x9.5
AEMFT-T-BP-650-1150-L	650-1150	1.0	75@460	50@1330	1.5	50.9x9.5x9.5
AEMFT-T-BP-900-960-L	900-960	3.0	50@855	50@1005	1.5	40.4x12.0x10
AEMFT-T-BP-940-1000-L	940-1000	3.2	55@895	55@1045	1.5	40.4x12.0x10
AEMFT-T-BP-985-1015-L	985-1015	3.0	65@900	65@1100	1.5	40.4x12.0x10
AEMFT-T-BP-1000-1160-L	1000-1160	1.0	60@680	75@1480	1.5	40.4x12.0x10
AEMFT-T-BP-950-1450-L	950-1450	0.8	40@700	40@1700	1.5	40.4x12.0x10
AEMFT-T-BP-1200-1400-L	1200-1400	1.5	60@1000	60@1600	1.5	40.4x12.0x10
AEMFT-T-BP-1100-1500-L	1100-1500	1.0	-	40@1700	1.5	40.4x12.0x10
AEMFT-T-BP-1200-1500-L	1200-1500	1.8	50@800	50@1830	1.5	40.4x12.0x10
AEMFT-T-BP-1241-1558-L	1241-1558	1.0	35@1100	-	1.5	40.4x12.0x10
AEMFT-T-BP-1000-2000-L	1000-2000	0.7	60@600	50@2400	1.5	40.4x12.0x10



RF LC Band Pass Filter



145MHz-5055MHz

P/N	1dB Pass Band (MHz)	I.L. at Center Freq. (dB) Max.	Rejection 1 (dB Min@MHz)	Rejection 2 (dB Min@MHz)	VSWR Typ.	Size (mm) (L x W x H)
AEMFT-T-BP-1460-1660-L	1460-1660	2.0	80@1230	80@1890	1.5	50.9x9.5x9.5
AEMFT-T-BP-1440-1960-L	1440-1960	1.3	-	60@2220	1.5	40.4x12.0x10
AEMFT-T-BP-1690-1890-L	1690-1890	1.3	80@945	70@1200	1.5	40.4x12.0x10
AEMFT-T-BP-2000-2200-L	2000-2200	1.8	75@1700	75@2500	1.5	50.9x9.5x9.5
AEMFT-T-BP-2000-2400-L	2000-2400	1.5	40@1850	40@2550	1.5	40.4x12.0x10
AEMFT-T-BP-2100-2500-L	2100-2500	1.9	60@1865	60@2735	1.5	40.4x12.0x10
AEMFT-T-BP-2400-2600-L	2400-2600	3.0	80@2100	80@2900	1.5	50.9x9.5x9.5
AEMFT-T-BP-2700-2900-L	2700-2900	3.2	35@2600	35@3000	1.5	50.9x9.5x9.5
AEMFT-T-BP-2850-3150-L	2850-3150	3.0	70@2500	70@3500	1.5	50.9x9.5x9.5
AEMFT-T-BP-3200-3400-L	3200-3400	2.8	70@2900	70@3700	1.5	50.9x9.5x9.5
AEMFT-T-BP-2998-4012-L	2998-4012	1.0	50@2500	70@5000	1.5	50.9x9.5x9.5
AEMFT-T-BP-3755-4435-L	3755-4435	2.6	80@2200	80@5000	1.5	50.9x9.5x9.5
AEMFT-T-BP-4850-5000-L	4850-5000	5.0	40@4700	40@5150	1.5	40.4x12.0x10
AEMFT-T-BP-4945-5055-L	4945-5055	6.0	80@4700	80@5300	1.5	50.9x9.5x9.5

Operating Temperature: -40 °C to +70 °C, Storage Temperature: -55 °C to +95 °C.

Customized available

Specification may change without notice



188 Technolgoy Drive, Unit H Irvine, CA 92618
TEL: 949-453-9888 ♦ FAX: 949-453-8889 ♦ Email: sales@aacix.com