




## Rectangular Waveguide Straight



P/N	Frequency Range (GHz)	Waveguide	VSWR	Length (mm)	Flange	Material
975STW-500	0.75-1.12	WR975	1.05	500	FDP9/FDM9	Al
770STW-500	0.96-1.45	WR770	1.05	500	FDP12/FDM12	Al
650STW-500	1.12-1.70	WR650	1.05	500	FDP14/FDM14	Al
510STW-500	1.45-2.20	WR510	1.05	500	FDP18/FDM18	Al
430STW-500	1.70-2.60	WR430	1.05	500	FDP22/FDM22	Al
340STW-500	2.20-3.30	WR340	1.05	500	FDP26/FDM26	Al
284STW-200	2.60-3.95	WR284	1.05	200	FDP32/FDM32	Al/Cu
229STW-200	3.30-4.90	WR229	1.05	200	FDP40/FDM40	Al/Cu
187STW-200	3.95-5.85	WR187	1.05	200	FDP48/FDM48	Al/Cu
159STW-200	4.90-7.05	WR159	1.05	200	FDP58/FDM58	Al/Cu
137STW-200	5.85-8.20	WR137	1.05	200	FDP70/FDM70	Al/Cu
112STW-200	7.05-10.0	WR112	1.05	200	FBP84/FBM84/FBE84	Al/Cu
90STW-100	8.20-12.4	WR90	1.05	100	FBP100/FBM100/FBE100	Al/Cu
90STW-1220	8.20-12.4	WR90	1.10	1220	FBP100/FBM100/FBE100	Al/Cu
75STW-100	10.0-15.0	WR75	1.05	100	FBP120/FBM120/FBE120	Al/Cu
62STW-100	12.4-18.0	WR62	1.05	100	FBP140/FBM140/FBE140	Al/Cu
62STW-2438	12.4-18.0	WR62	1.10	2438	FBP140/FBM140/FBE140	Al/Cu
51STW-100	15.0-22.0	WR51	1.05	100	FBP180/FBM180/FBE180	Al/Cu
42STW-100	18.0-26.5	WR42	1.05	100	FBP220/FBM220/FBE220	Al/Cu
34STW-100	22.0-33.0	WR34	1.05	100	FBP260/FBM260/FBE260	Al/Cu
28STW-100	26.5-40.0	WR28	1.05	100	FBP320/FBM320/FBE320	Al/Cu
22STW-50	33.0-50.0	WR22	1.10	50	FUGP400	Cu
19STW-50	40.0-60.0	WR19	1.10	50	FUGP500	Cu
15STW-50	50.0-75.0	WR15	1.10	50	FUGP620	Cu
12STW-50	60.0-90.0	WR12	1.10	50	FUGP740	Cu
10STW-50	75.0-110.0	WR10	1.10	50	FUGP900	Cu

Customized Available

Specification may change without notice

# AAC

American Accurate Components, Inc.

188 Technolgoy Drive, Unit H Irvine, CA 92618

TEL: 949-453-9888 ♦ FAX: 949-453-8889 ♦ Email: sales@aacix.com