



# SP5T Absorptive Switches



## SP5T Absorptive Switches

P/N	Freq. Range (GHz)	Insertion Loss (dB) Max.	Isolation (dB) Min.	VSWR Max.	Switching Speed (ns) Max.	Power Handling (W) Max.	Case
AEMPW-5A-0105	0.1-0.5	1.5	60	1.6	50	0.2	EPW501 EPW502
AEMPW-5A-0510	0.5-1.0	1.7	80	1.6	50	0.2	
AEMPW-5A-0520	0.5-2.0	2.0	60	1.7	50	0.2	
AEMPW-5A-1020	1-2	1.9	80	1.7	50	0.2	
AEMPW-5A-2040	2-4	2.3	80	1.7	50	0.2	
AEMPW-5A-2080	2-8	2.9	60	1.9	50	0.2	
AEMPW-5A-4080	4-8	2.7	60	1.7	50	0.2	
AEMPW-5A-80120	8-12	3.3	60	1.9	50	0.2	
AEMPW-5A-80180	8-18	4.0	60	1.9	50	0.2	
AEMPW-5A-120180	12-18	3.9	60	2.0	50	0.2	
AEMPW-5A-20180	2-18	4.2	60	2.2	50	0.2	

Specification may change without notice

### Outline Drawings for reference (Unit: mm)

