




SP7T Reflective Switches



SP7T Reflective Switches

P/N	Freq. Range (GHz)	Insertion Loss (dB) Max.	Isolation (dB) Min.	VSWR Max.	Switching Speed (ns) Max.	Power Handling (W) Max.	Case
AEMPW-7R-0105	0.1-0.5	1.6	60	1.5	50	0.5	EPW701 EPW702
AEMPW-7R-0510	0.5-1.0	1.5	60	1.5	50	0.5	
AEMPW-7R-0520	0.5-2.0	1.9	60	1.5	50	0.5	
AEMPW-7R-1020	1-2	1.7	80	1.5	50	0.5	
AEMPW-7R-2040	2-4	2.1	80	1.7	50	0.5	
AEMPW-7R-2080	2-8	2.7	60	1.7	50	0.5	
AEMPW-7R-4080	4-8	2.5	60	1.7	50	0.5	
AEMPW-7R-80120	8-12	3.1	60	2.0	50	0.5	
AEMPW-7R-80180	8-18	3.7	60	1.7	50	0.5	
AEMPW-7R-120180	12-18	3.9	60	2.0	50	0.5	
AEMPW-7R-20180	2-18	3.9	60	2.0	50	0.5	

Specification may change without notice

Outline Drawings for reference (Unit: mm)

