




SP8T Absorptive Switches



SP8T Absorptive Switches

P/N	Freq. Range (GHz)	Insertion Loss (dB) Max.	Isolation (dB) Min.	VSWR Max.	Switching Speed (ns) Max.	Power Handling (W) Max.	Case
AEMPW-8A-0105	0.1-0.5	2.1	60	1.7	50	0.2	EPW801 EPW802
AEMPW-8A-0510	0.5-1.0	2.1	80	1.5	50	0.2	
AEMPW-8A-0520	0.5-2.0	2.5	60	1.6	50	0.2	
AEMPW-8A-1020	1-2	2.5	80	1.5	50	0.2	
AEMPW-8A-2040	2-4	2.9	80	1.5	50	0.2	
AEMPW-8A-2080	2-8	2.9	60	1.7	50	0.2	
AEMPW-8A-4080	4-8	3.3	60	1.7	50	0.2	
AEMPW-8A-80120	8-12	3.9	60	2.0	50	0.2	
AEMPW-8A-80180	8-18	4.5	60	1.8	50	0.2	
AEMPW-8A-120180	12-18	4.3	60	2.0	50	0.2	
AEMPW-8A-20180	2-18	4.5	60	2.0	50	0.2	

Specification may change without notice

Outline Drawings for reference (Unit: mm)

