



## SPST Absorptive Switches



### SPST Absorptive Switches

P/N	Freq. Range (GHz)	Insertion Loss (dB) Max.	Isolation (dB) Min.	VSWR Max.	Switching Speed (ns) Max.	Power Handling (W) Max.	Case
AEMPW-1A-0105	0.1-0.5	1.2	60	1.5	50	0.2	EPW101
AEMPW-1A-0510	0.5-1.0	1.4	80	1.5	50	0.2	
AEMPW-1A-0520	0.5-2.0	1.2	60	1.5	50	0.2	
AEMPW-1A-1020	1-2	1.2	80	1.5	50	0.2	
AEMPW-1A-2040	2-4	1.5	80	1.5	50	0.2	
AEMPW-1A-2080	2-8	1.6	60	1.7	50	0.2	
AEMPW-1A-4080	4-8	1.8	60	1.6	50	0.2	
AEMPW-1A-80120	8-12	2.3	60	1.6	50	0.2	
AEMPW-1A-80180	8-18	2.5	60	1.7	50	0.2	
AEMPW-1A-120180	12-18	2.7	60	2.0	50	0.2	
AEMPW-1A-20180	2-18	3.0	60	2.0	50	0.2	

Specification may change without notice

### Outline Drawings for reference (Unit: mm)

