



Waveguide Circulator



P/N	Frequency Range (GHz)	Waveguide	Band Width (MHz)	Insertion Loss (dB)	Isolation (dB)	VSWR	Average Power (W)	Operating Temp. (°C)	Flange
284WCI	2.70-3.10	WR284	Full	0.5	20	1.25	200	-55~+85	FDP32/ FDM32
187WCI	4.4-5.0	WR187	Full	0.3	20	1.25	600	-55~+85	FDP48 FDM48
159WCI	5.4-5.8	WR159	Full	0.4	20	1.25	200	-55~+85	FDP58/ FDM58
112WCI	9.07-9.67	WR112	Full	0.5	20	1.25	300	-55~+85	FDP84/ FDM84
62WCI	12.36-16.7	WR62	Full	0.5	20	1.25	100	-55~+85	FBP140/ FBM140/ FBE140
42WCI	18.0-26.5	WR42	2000	0.4	20	1.25	50	-40~+70	FBP220/ FBM220/ FBE220
34WCI	24.0-27.0	WR34	Full	0.4	20	1.25	50	-40~+70	FBP260/ FBM260/ FBE260

Customized Available

Specification may change without notice



188 Technolgoy Drive, Unit H Irvine, CA 92618
 TEL: 949-453-9888 ♦ FAX: 949-453-8889 ♦ Email: sales@aacix.com