



Waveguide Diplexer



P/N	Frequency Range (GHz)	Waveguide	Insertion Loss (dB) Max.	Flatness (dB) Max.	Isolation (dB) Min.	Return Loss (dB) Min.	Port Type
AEWDX-112-7185	7.1-8.5	WR112	1.2	0.4	70	18	FBP84/SMA
AEWDX-75-10711745	10.7-11.745	WR75	1.2	0.4	70	18	FBP120/SMA
AEWDX-75-1275113248	12.751-13.248	WR75	1.2	0.4	70	18	FBP120/SMA
AEWDX-62-14515343	14.5-15.343	WR62	1.2	0.4	70	18	FBP140/SMA
AEWDX-42-17.67519735	17.675-19.735	WR42	1.2	0.4	60	18	FBP220
AEWDX-42-21223732	21.2-23.732	WR42	1.2	0.4	70	18	FBP220
AEWDX-42-245265	24.5-26.5	WR42	1.2	0.4	70	18	FBP220/SMA/2.92K
AEWDX-28-3704439452	37.044-39.452	WR28	1.3	0.4	65	20	FBP320
AEWDX-22-3754842532	37.548-42.532	WR28	1.5	0.6	50	15	FUGP400

Customized Available

Specification may change without notice



188 Technolgy Drive, Unit H Irvine, CA 92618
TEL: 949-453-9888 ♦ FAX: 949-453-8889 ♦ Email: sales@aacix.com