



Waveguide Fixed Attenuator

Waveguide Fixed Attenuator



P/N	Frequency Range (GHz)	Waveguide	Attenuation (dB)	VSWR	Flange	Material
650FWA-XX	1.12-1.70	WR650	3/6/10/20/30	1.25	FDP14/FDM14	Al
510FWA-XX	1.45-2.20	WR510	3/6/10/20/30	1.25	FDP18/FDM18	Al
430FWA-XX	1.70-2.60	WR430	3/6/10/20/30	1.25	FDP22/FDM22	Al
340FWA-XX	2.20-3.30	WR340	3/6/10/20/30	1.25	FDP26/FDM26	Al
284FWA-XX	2.60-3.95	WR284	3/6/10/20/30	1.25	FDP32/FDM32	Al/Cu
229FWA-XX	3.30-4.90	WR229	3/6/10/20/30	1.25	FDP40/FDM40	Al/Cu
187FWA-XX	3.95-5.85	WR187	3/6/10/20/30	1.25	FDP48/FDM48	Al/Cu
159FWA-XX	4.90-7.05	WR159	3/6/10/20/30	1.25	FDP58/FDM58	Al/Cu
137FWA-XX	5.85-8.20	WR137	3/6/10/20/30	1.25	FDP70/FDM70	Al/Cu
112FWA-XX	7.05-10.0	WR112	3/6/10/20/30	1.25	FBP84/FBM84/FBE84	Al/Cu
90FWA-XX	8.20-12.4	WR90	3/6/10/20/30	1.25	FBP100/FBM100/FBE100	Al/Cu
75FWA-XX	10.0-15.0	WR75	3/6/10/20/30	1.25	FBP120/FBM120/FBE120	Al/Cu
62FWA-XX	12.4-18.0	WR62	3/6/10/20/30	1.25	FBP140/FBM140/FBE140	Al/Cu
51FWA-XX	15.0-22.0	WR51	3/6/10/20/30	1.25	FBP180/FBM180/FBE180	Cu
42FWA-XX	18.0-26.5	WR42	3/6/10/20/30	1.25	FBP220/FBM220/FBE220	Cu
34FWA-XX	22.0-33.0	WR34	3/6/10/20/30	1.25	FBP260/FBM260/FBE260	Cu
28FWA-XX	26.5-40.0	WR28	3/6/10/20/30	1.25	FBP320/FBM320/FBE320	Cu
22FWA-XX	33.0-50.0	WR22	3/6/10/20/30	1.30	FUGP400	Cu
19FWA-XX	40.0-60.0	WR19	3/6/10/20/30	1.30	FUGP500	Cu
15FWA-XX	50.0-75.0	WR15	3/6/10/20/30	1.30	FUGP620	Cu
12FWA-XX	60.0-90.0	WR12	3/6/10/20/30	1.30	FUGP740	Cu
10FWA-XX	75.0-110.0	WR10	3/6/10/20/30	1.30	FUGP900	Cu

Specification may change without notice

AAC

American Accurate Components, Inc.

188 Technolgy Drive, Unit H Irvine, CA 92618
 TEL: 949-453-9888 ♦ FAX: 949-453-8889 ♦ Email: sales@aacix.com