



Waveguide Isolator



P/N	Frequency Range (GHz)	Waveguide	Band Width (MHz)	Insertion Loss (dB)	Isolation (dB)	VSWR	Average Power (W)	Flange
284WI	3.13-3.47	WR284	Full	0.5	20	1.25	200	FDP32/ FDM32
90WI-1	8.0-10.5	WR90	500	0.3	22	1.2	10	FBP100 FBM100 FBE100
90WI-2	10-10.3	WR90	Full	0.4	22	1.2	200	FBP100 FBM100 FBE100
75WI	12.5-13.5	WR75	500	0.4	22	1.2	10	FBP120 FBM120 FBE120
62WI-1	13-16	WR62	1000	0.4	20	1.2	100	FBP140 FBM140 FBE140
62WI-2	13-16	WR62	600	0.3	22	1.2	30	FBP140 FBM140 FBE140
51WI	16.0-17.0	WR51	500	0.5	25	1.18	100	FBP180 FBM180 FBE180
42WI-1	18-26.5	WR42	1000	0.4	20	1.25	10	FBP220 FBM220 FBE220
42WI-2	21.0-23.0	WR42	2000	0.5	20	1.25	10	FBP220 FBM220 FBE220

Customized available

Specification may change without notice